

Received: 06/28/2019		Completed: 08/02/2019		Letter: N	JR	P.O.#:	Test Report #: 3-33244-0-
Client's Identification	Lot No.: 001. Treated. Date of Mfg.: 05/21/2019. Composition: [REDACTED] Weight: 2,20 lbs. Product End Use: 12/31/2019.						
Tested For: Camille E, Ferber Ferber Group LLC 16192 Coastal Hwy Lewes, DE 19958				Key Test: NFPA 701-2019 TM#1 275 Tel: 1-(864)-778-8888 Ext: Fax: 1-()- -			

REMARKS:

- ☒ Flames did not project above the top of the specimen.
- ☐ Flames projected above the top of the specimen; Specimen #'s _____
- ☒ Other: Partical board cut to 15" x 6" x 0.403" submitted by client for TM#1.

FAILURE CRITERIA: As cited by NFPA 701 - 2019 Edition Test Method #1


Afterflame	Flaming Drip/Debris (Mean)	Weight Loss (percent)	
		Mean	Individual Specimen
*	Exceeds 2 seconds	Exceeds 40%	Exceeds Mean + 3 SD

CONCLUSION: Based on the Results on page 1 and the above Failure Criteria cited by NFPA 701 - 2019 Edition Test Method #1, the item tested:

- ☒ Passes; ☐ Fails; ☐ Requires testing of 10 additional specimens
i.e. only one individual specimen failure was noted

* Afterflame is required to be recorded; however, the NFPA document does not factor it into the Failure Criteria reporting requirements. It should be noted that excessive afterflames could be cause for rejection by local fire authorities performing "match" field tests.

CERTIFICATION: I certify that the above results were obtained after testing specimens in accordance with the procedures and equipment specified above.



AUTHORIZED SIGNATURE
SGS GOVMARK
/jab /gb

AUG 06 2019